



## Through-bolt expansion anchor with controlled torque, for use in non cracked concrete

MTH-A4

ETA Assessed Option 7. A4 Stainless shaft. A4 Stainless clip.



## PRODUCT INFORMATION

### DESCRIPTION

Metallic anchor, with male thread, expansion by controlled torque.

### OFFICIAL DOCUMENTATION

- AVCP-1219-CPR-0006.
- ETA 05/0242 Option 7.
- Declaration of Performance DoP MTH-A4
- MFPA Fire Protection Assessment.

### SIZES

M6x45 to M20x220.

### DESIGN LOAD RANGE

From 6,0 to 27,8 kN [standard depth].  
From 5,0 to 8,9 kN [reduced depth].



### BASE MATERIAL

Concrete class from C20/25 to C50/60 non-cracked.



Stone

Concrete

Reinforced concrete

### ASSESSMENTS

- Option 7 [non-cracked concrete].



05  
Técnicas Expansivas S.L.  
Segador 13. Logroño. Spain  
ETA 05/0242  
1219  
Structural fixings in non  
cracked concrete

### CHARACTERISTICS AND BENEFITS

- Easy installation.
- Use in non-cracked concrete.
- Use for medium-heavy duty loads.
- Pre-installation or through the drill-hole of the fixture.
- Variety of lengths and diameters: flexibility in assembly.
- For static and quasi-static loads.
- Two installation depths in M8, M10 and M12 allowing the use in thick anchor plates or in los thickness base materials.
- Available at INDEXcal.
- Version in A4 Stainless steel (AISI 316).
- Available at INDEXcal.



### MATERIALS

Shaft: A4 grade stainless steel.

Washer: A4 grade stainless steel.

Nut: A4 grade stainless steel.



Clip: AA4 grade stainless steel.

### APPLICATIONS

- Coastal areas.
- Industrial areas.
- Food industries.
- Curtain walls.
- Fixings in tunnels.
- Pipe supports.
- Rehabilitation of facades.
- For outdoor use in general.






## MECHANICAL PROPERTIES

			M6	M8	M10	M12	M16	M20
Cone area section								
$A_s$	(mm <sup>2</sup> )	Cone area section	14,5	27,3	49,0	70,9	122,7	201,1
$f_{u,s}$	(N/mm <sup>2</sup> )	Characteristic tension resistance	700	700	700	700	700	700
$f_{y,s}$	(N/mm <sup>2</sup> )	Yield strength	500	500	500	500	500	500
Threaded area section								
$A_s$	(mm <sup>2</sup> )	Cone area section	20,1	36,6	58,0	84,3	157,0	245,0
$f_{u,s}$	(N/mm <sup>2</sup> )	Characteristic tension resistance	600	600	600	600	600	600
$f_{y,s}$	(N/mm <sup>2</sup> )	Yield Strength	400	400	400	400	400	400

## INSTALLATION DATA


SIZE	M6	M8	M10	M12	M16	M20			
Code	MIA406XXX	MIA408XXX	MIA410XXX	MIA412XXX	MIA416XXX	MIA420XXX			
$d_0$	Nominal diameter of drill bit	[mm]	6	8	10	12	16	20	
$T_{ins}$	Installation torque moment	[Nm]	7	20	35	60	120	240	
$d_f \leq$	Diameter of clearance hole in the fixture	[mm]	7	9	12	14	18	22	
Standard depth	$h_1$	Minimum drill hole depth	[mm]	55	65	75	85	110	135
	$h_{nom}$	Installation depth	[mm]	49,5	59,5	66,5	77	103,5	125
	$h_{ef}$	Effective embedment depth	[mm]	40	48	55	65	84	103
	$h_{min}$	Minimum base material thickness	[mm]	100	100	110	130	168	206
	$t_{fix}$	Maximum thickness of fixture*	[mm]	L - 58	L - 70	L - 80	L - 92	L - 122	L - 147
	$S_{cr,N}$	Critical spacing	[mm]	120	144	165	195	252	309
	$C_{cr,N}$	Critical edge distance	[mm]	60	72	83	98	126	155
	$S_{cr,sp}$	Critical distance (splitting)	[mm]	160	192	220	260	336	412
	$C_{cr,sp}$	Critical edge distance (splitting)	[mm]	80	96	110	130	168	206
Reduced depth	$h_1$	Minimum drill hole depth	[mm]	-	50	60	70	-	-
	$h_{nom}$	Installation depth	[mm]	-	46,5	53,5	62	-	-
	$h_{ef}$	Effective embedment depth	[mm]	-	35	42	50	-	-
	$h_{min}$	Minimum base material thickness	[mm]	-	100	100	100	-	-
	$t_{fix}$	Maximum thickness of fixture*	[mm]	-	L-57	L-67	L-77	-	-
	$S_{cr,N}$	Critical spacing	[mm]	-	105	126	150	-	-
	$C_{cr,N}$	Critical edge distance	[mm]	-	53	63	75	-	-
	$S_{cr,sp}$	Critical distance (splitting)	[mm]	-	140	168	200	-	-
	$C_{cr,sp}$	Critical edge distance (splitting)	[mm]	-	70	84	100	-	-
$S_{min}$	Minimum spacing	[mm]	50	65	70	85	110	135	
$C_{min}$	Minimum edge distance	[mm]	50	65	70	85	110	135	
SW	Installation wrench		10	13	17	19	24	30	

\*L = Total anchor length





Code	INSTALLATION PRODUCTS
	Hammer drill
BHDSXXXXX	Concrete Drill bits
MOBOMBA	Blow pump
MORCEPKIT	Cleaning Brush
DOMTAXX	Installation hammering tool
	Torque wrench
	Hexagonal socket



MTH-A4

## Resistances in C20/25 concrete for an isolated anchor, without effects of edge distance or spacing

Characteristic Resistance $N_{Rk}$ y $V_{Rk}$																	
TENSION							SHEAR										
Size			M6	M8	M10	M12	M16	M20	Size			M6	M8	M10	M12	M16	M20
$N_{Rk}$	Standard depth	[kN]	10,1	12	16	25	35	50	$V_{Rk}$	Standard depth	[kN]	6,0	10,9	17,4	25,2	47,1	73,5
$N_{Rk}$	Reduced depth	[kN]	-	9	12	16	-	-	$V_{Rk}$	Reduced depth	[kN]	-	10,4	13,7	17,8	-	-

Design Resistance $N_{Rd}$ y $V_{Rd}$																	
TENSION							SHEAR										
Size			M6	M8	M10	M12	M16	M20	Size			M6	M8	M10	M12	M16	M20
$N_{Rd}$	Standard depth	[kN]	6,0	8,0	8,9	13,9	19,4	27,8	$V_{Rd}$	Standard depth	[kN]	3,9	7,1	11,4	16,6	30,1	48,3
$N_{Rd}$	Reduced depth	[kN]	-	5,0	6,7	8,9	-	-	$V_{Rd}$	Reduced depth	[kN]	-	7,0	9,1	11,9	-	-

Maximum Loads Recommended $N_{rec}$ y $V_{rec}$																	
TENSION							SHEAR										
Size			M6	M8	M10	M12	M16	M20	Size			M6	M8	M10	M12	M16	M20
$N_{rec}$	Standard depth	[kN]	4,3	5,7	6,3	9,9	13,9	19,8	$V_{rec}$	Standard depth	[kN]	2,8	5,1	8,2	11,8	22,1	34,5
$N_{rec}$	Reduced depth	[kN]	-	3,6	4,8	6,4	-	-	$V_{rec}$	Reduced depth	[kN]	-	4,9	6,5	8,5	-	-

## Simplified calculation method

### European Technical Assessment ETA 05/0242

Simplified version of the calculation method according to ETAG 001, annex C. Resistance is calculated according to the data shown in assessment ETA 05/0242.

The calculation method is based on the following simplification:  
Different loads do not act on individual anchors, without eccentricity.

- Influence of concrete strength.
- Influence of edge distance.
- Influence of spacing between anchors.
- Influence of reinforcements.
- Influence of base material thickness.
- Influence of load application angle.
- Valid for a group of two anchors.



### INDEXcal

For a more accurate calculation and to take more constructive provisions into account, we recommend using our calculation program INDEXcal. It may be easily downloaded from our website [www.indexfix.com](http://www.indexfix.com)




## MTH-A4


### TENSION LOADS

- Steel design resistance:  $N_{Rd,s}$
- Pull-out design resistance:  $N_{Rd,p} = N_{Rd,p}^o \cdot \Psi_c$
- Concrete cone design resistance:  $N_{Rd,c} = N_{Rd,c}^o \cdot \Psi_b \cdot \Psi_{s,N} \cdot \Psi_{c,N} \cdot \Psi_{re,N}$
- Concrete splitting design resistance:  $N_{Rd,sp} = N_{Rd,c}^o \cdot \Psi_b \cdot \Psi_{s,sp} \cdot \Psi_{c,sp} \cdot \Psi_{re,N} \cdot \Psi_{h,sp}$

Steel Design resistance								
$N_{Rd,s}$								
Size		M6	M8	M10	M12	M16	M20	
$N_{Rd}^o$	Standard depth	[kN]	6,0	11,4	20,4	29,5	51,1	83,8




Pull-out design resistance								
$N_{Rd,p} = N_{Rd,p}^o \cdot \Psi_c$								
Size		M6	M8	M10	M12	M16	M20	
$N_{Rd,p}^o$	Standard depth	[kN]	-*	8,0	8,9	13,9	19,4	27,8
$N_{Rd,p}^o$	Reduced depth	[kN]	-	5,0	6,7	8,9	-	-



\* Pull-out failure is not decisive.

Concrete cone design resistance								
$N_{Rd,c} = N_{Rd,c}^o \cdot \Psi_b \cdot \Psi_{s,N} \cdot \Psi_{c,N} \cdot \Psi_{re,N}$								
Concrete splitting design resistance*								
$N_{Rd,sp} = N_{Rd,c}^o \cdot \Psi_b \cdot \Psi_{s,sp} \cdot \Psi_{c,sp} \cdot \Psi_{re,N} \cdot \Psi_{h,sp}$								
Size		M6	M8	M10	M12	M16	M20	
$N_{Rd,c}^o$	Standard depth	[kN]	8,5	11,2	11,4	14,7	21,6	29,3
$N_{Rd,c}^o$	Reduced depth	[kN]	-	5,8	7,6	9,9	-	-




\*Concrete splitting design resistance must only be considered for non-cracked concrete.




## Coefficients of influence

**MTH-A4**Influence of concrete strength resistance in pul-out failure  $\Psi_c$ 

	M6	M8	M10	M12	M16	M20
$\Psi_c$	C 20/25		1,00			
	C 30/37		1,22			
	C 40/50		1,41			
	C 50/60		1,55			

Influence of concrete strength in concrete cone and splitting failure  $\Psi_b$ 


	M6	M8	M10	M12	M16	M20
$\Psi_b$	C 20/25		1,00			
	C 30/37		1,22			
	C 40/50		1,41			
	C 50/60		1,55			



$$\Psi_b = \sqrt{\frac{f_{ck,cube}}{25}} \geq 1$$



## MTH-A4



$$\Psi_{s,N} = 0,5 + \frac{S}{2 \cdot S_{cr,N}} \leq 1$$

s [mm]	Influence of spacing (concrete cone) $\Psi_{s,N}$					
	MTH-A4. Standard depth					
M6	M8	M10	M12	M16	M20	
50	0,71					
55	0,73					
60	0,75					
65	0,77	0,73				
70	0,79	0,74	0,71			
80	0,83	0,78	0,74			
85	0,85	0,80	0,76	0,72		
90	0,88	0,81	0,77	0,73		
100	0,92	0,85	0,80	0,76		
105	0,94	0,86	0,82	0,77		
110	0,96	0,88	0,83	0,78	0,72	
120	1,00	0,92	0,86	0,81	0,74	
125		0,93	0,88	0,82	0,75	
126		0,94	0,88	0,82	0,75	
128		0,94	0,89	0,83	0,75	
130		0,95	0,89	0,83	0,76	
135		0,97	0,91	0,85	0,77	0,72
144		1,00	0,94	0,87	0,79	0,73
150			0,95	0,88	0,80	0,74
165			1,00	0,92	0,83	0,77
170				0,94	0,84	0,78
180				0,96	0,86	0,79
195				1,00	0,89	0,82
200					0,90	0,82
210					0,92	0,84
220					0,94	0,86
225					0,95	0,86
252					1,00	0,91
255						0,91
260						0,92
300						0,99
309						1,00

Value without reduction = 1

s [mm]	MTH-A4. Reduced depth					
	M6	M8	M10	M12	M16	M20
65		0,81				
70		0,83	0,78			
80		0,88	0,82			
85		0,90	0,84	0,78		
90		0,93	0,86	0,80		
100		0,98	0,90	0,83		
105		1,00	0,92	0,85		
110			0,94	0,87		
120			0,98	0,90		
125			1,00	0,92		
126			1,00	0,92		
128				0,93		
130				0,93		
135				0,95		
144				0,98		
150				1,00		


Invalid value

Influence of spacing (concrete splitting)  $\Psi_{s,sp}$ 

s [mm]	MTH-A4. Standard depth					
	M6	M8	M10	M12	M16	M20
50	0,66					
55	0,67					
60	0,69					
65	0,70	0,67				
70	0,72	0,68	0,66			
80	0,75	0,71	0,68			
85	0,77	0,72	0,69	0,66		
90	0,78	0,73	0,70	0,67		
100	0,81	0,76	0,73	0,69		
110	0,84	0,79	0,75	0,71	0,66	
125	0,89	0,83	0,78	0,74	0,69	
128	0,90	0,83	0,79	0,75	0,69	
135	0,92	0,85	0,81	0,76	0,70	0,66
140	0,94	0,86	0,82	0,77	0,71	0,67
150	0,97	0,89	0,84	0,79	0,72	0,68
160	1,00	0,92	0,86	0,81	0,74	0,69
165		0,93	0,88	0,82	0,75	0,70
168		0,94	0,88	0,82	0,75	0,70
180		0,97	0,91	0,85	0,77	0,72
192		1,00	0,94	0,87	0,79	0,73
200			0,95	0,88	0,80	0,74
210			0,98	0,90	0,81	0,75
220			1,00	0,92	0,83	0,77
260				1,00	0,89	0,82
288					0,93	0,85
300					0,95	0,86
336					1,00	0,91
350						0,92
412						1,00

Invalid value

MTH-A4



$$\Psi_{s,sp} = 0,5 + \frac{S}{2 \cdot S_{cr,sp}} \leq 1$$


Value without reduction = 1

s [mm]	MTH-A4. Reduced depth					
	M6	M8	M10	M12	M16	M20
65		0,73				
70		0,75	0,71			
80		0,79	0,74			
85		0,80	0,75	0,71		
90		0,82	0,77	0,73		
100		0,86	0,80	0,75		
110		0,89	0,83	0,78		
125		0,95	0,87	0,81		
128		0,96	0,88	0,82		
135		0,98	0,90	0,84		
140		1,00	0,92	0,85		
150			0,95	0,88		
160			0,98	0,90		
165			0,99	0,91		
168			1,00	0,92		
180				0,95		
192				0,98		
200				1,00		

Invalid value



## MTH-A4



$$\Psi_{c,sp} = 0,35 + \frac{0,5 \cdot c}{C_{cr,sp}} + \frac{0,15 \cdot c^2}{C_{cr,sp}^2} \leq 1$$

c [mm]	Influence of concrete edge distance (splitting) $\Psi_{c,sp}$					
	MTH-A4. Standard depth					
M6	M8	M10	M12	M16	M20	
50	0,72					
60	0,81					
65	0,86	0,76				
70	0,90	0,79	0,73			
75	0,95	0,83	0,76			
80	1,00	0,87	0,79			
83		0,89	0,81			
84		0,90	0,82			
85		0,91	0,83	0,74		
90		0,95	0,86	0,77		
96		1,00	0,90	0,80		
100			0,93	0,82		
105			0,96	0,85		
110			1,00	0,88	0,74	
125				0,97	0,81	
128				0,99	0,82	
130				1,00	0,83	
135					0,85	0,74
144					0,89	0,77
150					0,92	0,79
168					1,00	0,86
175						0,88
180						0,90
206						1,00

Value without reduction = 1


c [mm]	MTH-A4. Reduced depth					
	M6	M8	M10	M12	M16	M20
50		0,78				
60		0,89	0,78			
65		0,94	0,83			
70		1,00	0,87			
75			0,92			
80			0,96			
83			0,99	0,87		
84			1,00	0,88		
85				0,88		
90				0,92		
96				0,97		
100				1,00		

Value without reduction = 1



Influence of concrete edge distance (concrete cone) $\Psi_{c,N}$						
c [mm]	MTH-A4. Standard depth					
	M6	M8	M10	M12	M16	M20
50	0,87					
53	0,91					
60	1,00					
63						
65	0,92					
70	0,98	0,88				
72	1,00	0,90				
75		0,92				
80		0,97				
83		1,00				
85			0,90			
90			0,94			
98			1,00			
100						
105						
110				0,90		
113				0,92		
125				0,99		
126				1,00		
128						
135					0,90	
150					0,97	
155					1,00	

**Value without reduction = 1**

**MTH-A4**

$$\Psi_{c,N} = 0,35 + \frac{0,5 \cdot c}{C_{cr,N}} + \frac{0,15 \cdot c^2}{C_{cr,N}^2} \leq 1$$


c [mm]	MTH-A4. Reduced depth					
	M6	M8	M10	M12	M16	M20
65		1,00				
70			1,00			
72						
75						
80						
83						
85				1,00		

**Value without reduction = 1**

**Invalid value**




## MTH-A4



$$\Psi_{re,N} = 0,5 + \frac{h_{ef}}{200} \leq 1$$

Influence of reinforcements $\Psi_{re,N}$						
$\Psi_{re,N}$	MTH-A4. Standard depth					
	M6	M8	M10	M12	M16	M20
	0,70	0,74	0,77	0,82	0,92	1,00
MTH-A4. Reduced depth						
	M6	M8	M10	M12	M16	M20
	-	0,67	0,71	0,75	-	-

\*This factor only applies for a high density of reinforcements. If in the area of the anchor there are reinforcements with a distancing of  $\geq 150$  mm (any diameter) or with a diameter  $\leq 10$  mm and a distancing of  $\geq 100$  mm, a  $f_{re,N} = 1$  factor may be applied.



Influence of base material thickness $\Psi_{h,sp}$											
$\Psi_{h,sp}$	MTH-A4										
	h/hef	2,00	2,20	2,40	2,60	2,80	3,00	3,20	3,40	3,60	$\geq 3,68$
$\Psi_{h,sp}$	1,00	1,07	1,13	1,19	1,25	1,31	1,37	1,42	1,48	1,50	


$$\Psi_{h,sp} = \left( \frac{h}{2 \cdot h_{ef}} \right)^{2/3} \leq 1,5$$

## SHEAR LOADS

- Steel design resistance without lever arm:  $V_{Rd,s}$
- Pry-out design resistance:  $V_{Rd,cp} = k \cdot N^o_{Rd,c}$
- Concrete edge design resistance:  $V_{Rd,c} = V^o_{Rd,c} \cdot \Psi_b \cdot \Psi_{se,V} \cdot \Psi_{c,V} \cdot \Psi_{re,V} \cdot \Psi_{\alpha,V} \cdot \Psi_{h,V}$


### Steel design resistance

$V_{Rd,s}$								
Size		M6	M8	M10	M12	M16	M20	
$V_{Rd,s}$	Standard depth	[kN]	3,9	7,2	11,4	16,6	31,0	48,4
$V_{Rd,s}$	Reduced depth	[kN]	-	7,2	11,4	16,6	-	-



### Pry-out design resistance\*


$V_{Rd,cp} = k \cdot N^o_{Rd,c}$					
Size	M6	M8	M10	M12	M20
k (Standard depth)	1	1	1	2	2
k (Reduced depth)	-	1	1	1	-



\*  $N^o_{Rd,c}$  Concrete cone design resistance for tension loads

### Concrete edge resistance

$V_{Rd,c} = V^o_{Rd,c} \cdot \Psi_b \cdot \Psi_{se,V} \cdot \Psi_{c,V} \cdot \Psi_{re,V} \cdot \Psi_{\alpha,V} \cdot \Psi_{h,V}$								
Size	M6	M8	M10	M12	M16	M20		
$V^o_{Rd,c}$	Standard depth	[kN]	4,6	6,2	7,7	10,2	15,6	21,8
$V^o_{Rd,c}$	Reduced depth	[kN]	-	3,7	4,9	6,6	-	-






## Coefficients of influence



MTH-A4

Influence of concrete strength in concrete edge failure $\Psi_b$							
		M6	M8	M10	M12	M16	M20
$\Psi_b$	C 20/25	1,00					
	C 30/37	1,22					
	C 40/50	1,41					
	C 50/60	1,55					



$$\Psi_b = \sqrt{\frac{f_{ck,cube}}{25}} \geq 1$$

Influence of edge distance and spacing $\Psi_{se,V}$																	
FOR ONE ANCHOR ONLY																	
c/h <sub>ef</sub>	0,50	0,75	1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,50	5,00
Isolated	0,35	0,65	1,00	1,40	1,84	2,32	2,83	3,38	3,95	4,56	5,20	5,86	6,55	7,26	8,00	9,55	11,18
FOR TWO ANCHORS																	
s/c	0,50	0,75	1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,50	5,00
1,0	0,24	0,43	0,67	0,93	1,22	1,54	1,89	2,25	2,64	3,04	3,46	3,91	4,37	4,84	5,33	6,36	7,45
1,5	0,27	0,49	0,75	1,05	1,38	1,74	2,12	2,53	2,96	3,42	3,90	4,39	4,91	5,45	6,00	7,16	8,39
2,0	0,29	0,54	0,83	1,16	1,53	1,93	2,36	2,81	3,29	3,80	4,33	4,88	5,46	6,05	6,67	7,95	9,32
2,5	0,32	0,60	0,92	1,28	1,68	2,12	2,59	3,09	3,62	4,18	4,76	5,37	6,00	6,66	7,33	8,75	10,25
≥3,0	0,35	0,65	1,00	1,40	1,84	2,32	2,83	3,38	3,95	4,56	5,20	5,86	6,55	7,26	8,00	9,55	11,18




$$\Psi_{se,V} = \left( \frac{c}{h_{ef}} \right)^{1,5}$$

$$\Psi_{se,V} = \left( \frac{c}{h_{ef}} \right)^{1,5} \cdot \left( 1 + \frac{s}{3 \cdot c} \right) \cdot 0,5 \leq \left( \frac{c}{h_{ef}} \right)^{1,5}$$



## MTH-A4




$$\Psi_{c,v} = \left( \frac{d}{c} \right)^{0,20}$$


c [mm]	Influence of concrete edge distance $\Psi_{c,v}$					
	MTH-A4					
	M6	M10	M10	M12	M16	M20
40						
45						
50	0,65					
55	0,64					
60	0,63					
65	0,62	0,66				
70	0,61	0,65	0,68			
80	0,60	0,63	0,66			
85	0,59	0,62	0,65	0,68		
90	0,58	0,62	0,64	0,67		
100	0,57	0,60	0,63	0,65	0,67	
105	0,56	0,60	0,62	0,65	0,67	
110	0,56	0,59	0,62	0,64	0,66	0,68
120	0,55	0,58	0,61	0,63	0,65	0,67
125	0,54	0,58	0,60	0,63	0,65	0,66
130	0,54	0,57	0,60	0,62	0,64	0,66
135	0,54	0,57	0,59	0,62	0,64	0,65
140	0,53	0,56	0,59	0,61	0,63	0,65
150	0,53	0,56	0,58	0,60	0,62	0,64
160	0,52	0,55	0,57	0,60	0,61	0,63
170	0,51	0,54	0,57	0,59	0,61	0,62
175	0,51	0,54	0,56	0,59	0,60	0,62
180	0,51	0,54	0,56	0,58	0,60	0,62
190	0,50	0,53	0,55	0,58	0,59	0,61
200	0,50	0,53	0,55	0,57	0,59	0,60
210	0,49	0,52	0,54	0,56	0,58	0,60
220	0,49	0,52	0,54	0,56	0,58	0,59
230	0,48	0,51	0,53	0,55	0,57	0,59
240	0,48	0,51	0,53	0,55	0,57	0,58
250	0,47	0,50	0,53	0,54	0,56	0,58
260	0,47	0,50	0,52	0,54	0,56	0,57
270	0,47	0,49	0,52	0,54	0,55	0,57
280	0,46	0,49	0,51	0,53	0,55	0,56
290	0,46	0,49	0,51	0,53	0,55	0,56
300	0,46	0,48	0,51	0,53	0,54	0,56



Influence of reinforcements $\Psi_{re,v}$			
	Without perimetral reinforcements	Perimetral reinforcements $\geq \varnothing 12 \text{ mm}$	Perimetral reinforcements with brackets $\leq 100 \text{ mm}$
Non-cracked concrete	1	1	1




Influence of load application angle $\Psi_{\alpha,v}$										
Angle, $\alpha(^{\circ})$	0°	10°	20°	30°	40°	50°	60°	70°	80°	90°
$\Psi_{\alpha,v}$	1,00	1,01	1,05	1,13	1,24	1,40	1,64	1,97	2,32	2,50



$$\Psi_{\alpha,v} = \sqrt{\frac{1}{(\cos \alpha_v)^2 + \left(\frac{\sin \alpha_v}{2,5}\right)^2}} \geq 1$$

Influence of base material thickness $\Psi_{h,v}$										
MTH-A4										
$h/c$	0,15	0,30	0,45	0,60	0,75	0,90	1,05	1,20	1,35	$\geq 1,5$
$\Psi_{h,v}$	0,32	0,45	0,55	0,63	0,71	0,77	0,84	0,89	0,95	1,00



$$\Psi_{h,v} = \left( \frac{h}{1,5 \cdot c} \right)^{0,5} \geq 1,0$$



## MTH-A4

## FIRE RESISTANCE

Characteristic Resistance*												
	TENSION						SHEAR					
	M6	M8	M10	M12	M16	M20	M6	M8	M10	M12	M16	M20
RF30	-	0,8	1,5	2,4	4,5	7,0	-	0,8	1,5	2,4	4,5	7,0
RF60	-	0,7	1,2	2,0	3,6	5,7	-	0,7	1,2	2,0	3,6	5,7
RF90	-	0,5	1,0	1,5	2,7	4,3	-	0,5	1,0	1,5	2,7	4,3
RF120	-	0,5	0,8	1,2	2,3	3,6	-	0,5	0,8	1,2	2,3	3,6

\*The safety factor for design resistance under fire exposure is  $\gamma_{M,ff}=1$  (in absence of other national regulations). As a result the Characteristic Resistance is the same as Design Resistance.

Maximum Load Recommended												
	TENSION						SHEAR					
	M6	M8	M10	M12	M16	M20	M6	M8	M10	M12	M16	M20
RF30	-	0,6	1,1	1,7	3,2	5,0	-	0,6	1,1	1,7	3,2	5,0
RF60	-	0,5	0,9	1,4	2,6	4,0	-	0,5	0,9	1,4	2,6	4,0
RF90	-	0,4	0,7	1,1	2,0	3,1	-	0,4	0,7	1,1	2,0	3,1
RF120	-	0,3	0,6	0,9	1,6	2,6	-	0,3	0,6	0,9	1,6	2,6

- Fire resistance values are not covered by ETA.

## RANGE

Code	Size	Maximum thickness of fixture	Axle letter (length)	☒	☒	Code	Size	Maximum thickness of fixture	Axle letter (length)	☒	☒
• MIA406045	M6 x 45 Ø6	1	A	200	1.200	• MIA412075	M12 x 75 Ø12	5	C	50	300
MIA406060	M6 x 60 Ø6	2	B	200	1.200	MIA412090	M12 x 90 Ø12	13	D	50	200
MIA406080	M6 x 80 Ø6	22	D	200	1.200	MIA412110	M12 x 110 Ø12	12	F	50	200
• MIA408050	M8 x 50 Ø8	4	A	100	800	MIA412140	M12 x 140 Ø12	42	I	50	200
MIA408075	M8 x 75 Ø8	5	C	100	600	• MIA416090	M16 x 90 Ø16	4	D	25	150
MIA408090	M8 x 90 Ø8	20	E	100	600	MIA416145	M16 x 145 Ø16	23	I	25	100
MIA408115	M8 x 115 Ø8	45	G	100	400	MIA416170	M16 x 170 Ø16	48	K	25	75
MIA410070	M10 x 70 Ø10	3	C	100	400	• MIA420120	M20 x 120 Ø20	5	G	20	80
MIA410090	M10 x 90 Ø10	10	D	100	400	MIA420170	M20 x 170 Ø20	23	K	20	80
MIA410120	M10 x 120 Ø10	40	G	50	300	MIA420220	M20 x 220 Ø20	73	O	20	60
MIA410150	M10 x 150 Ø10	70	I	50	200						

- Non assessed sizes. Resistance values and installation data are not applicable to these references. For further information, please contact Technical Department.